

Product Specifications For C32B Twin Turbo



Engine Specifications

Application	Yachting
-------------	----------

Stroke	162 mm
--------	--------

Engine

Speed Range	2300 rpm
-------------	----------

Emissions	IMO II, U.S. EPA Tier 3 Recreational, RCD, China Stage II
-----------	---

Aspiration	TTA
------------	-----

Bore	145 mm
------	--------

Stroke	162 mm
--------	--------

Displacement	32.1 l
--------------	--------

Rotation from Flywheel End	Counterclockwise
----------------------------	------------------

Configuration	Vee 12, 4-Stroke-Cycle Diesel
---------------	-------------------------------

Dimensions & Weights

Width	1469 mm
-------	---------

Dry Weight	3145 kg
------------	---------

Length	2106 mm
--------	---------

Height	1445 mm
--------	---------

Ratings

Power Range	2000 bhp (1491 bkW)
-------------	---------------------

C32B Twin Turbo Standard Equipment

Standard Equipment

ADEM VI Electronic Control Module
Air Cleaner / Fumes Disposal
Electronic Diagnostics and Fault Logging
Engine and Transmission Monitoring
Sea Water Aftercooler
Titanium Plate Heat Exchanger with Expansion Tank
Gear-driven JW and SW pumps
Water-cooled Exhaust Manifolds and Turbochargers
MEUI-C Fuel System
Fuel Priming and Transfer Pump
250-hr Oil Pan (Shallow Sump)
RH or LH Service Side Options

C32B Twin Turbo Optional Equipment

Optional Attachments

120V or 240V Jacket Water Heater
SAE A or B PTO (LH or RH rear)
75A or 105A Alternator
Spray Shielding